Ed. Berlin, Heidelberg: Springer Berlin Heidelberg, 2001, pp. 280–300.

[10] A. Machanavajjhala, J. Gehrke, D. Kifer, and M. Venkitasubramaniam, "L-diversity: privacy beyond k-anonymity," in 22nd International Conference on Data Engineering (ICDE'06), April 2006, pp. 24–24.

[11] L. SWEENEY, "k-anonymity: A model for protecting privacy," International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems, vol. 10, no. 05, pp. 557–570, 2002. [Online]. http://www.worldscientific.com/doi/abs/10.1142/S0218488502001648

[12] Y. Bengio, "Learning deep architectures for AI," Found. Trends Mach. Learn., vol. 2, no. 1, pp. 1–127, Jan. 2009, (Access Date: 16 July, 2016). [Online]. Available: http://dx.doi.org/10.1561/2200000006

[13] Q. Le, "Building high-level features using large scale unsupervised learning," in Acoustics, Speech and Signal Processing (ICASSP), 2013 IEEE International Conference on, May 2013, pp. 8595–8598.

[14] I. J. Goodfellow, D. Warde-Farley, M. Mirza, A. Courville, and Y. Bengio, "Maxout Networks," ArXiv e-prints, Feb. 2013.

[15] A. Niimi, "Deep learning for credit card data analysis," in World Congress on Internet Security (WorldCIS-2015), Dublin, Ireland, Oct. 2015, pp. 73–77.

[16] A. Niimi, "Deep learning for real credit card data," in Fuzzy Systems and Data Mining III, Proceedings of FSDM 2017, Hualien, Taiwan, Nov. 2017, pp. 303–310.

[17] B. Wallace, K. Small, C. Brodley, and T. Trikalinos, Class imbalance, redux, 2011, pp. 754–763.

[18] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "Smote: Synthetic minority over-sampling technique," Journal of Artificial Intelligence Research, vol. 16, pp. 321–357, 2002.

[19] Cornell anonymization toolkit. (Access Date: 31 January, 2017). [Online]. Available: https://sourceforge.net/projects/anony-toolkit/

[20] Utd anonymization toolbox. (Access Date: 31 January, 2017). [Online]. Available: http://www.cs.utdallas.edu/dspl/cgi-bin/toolbox/index.php

11. Acknowledgements